



## SLOT WEDGE NMNM 4-PLY LAMINATE (WHITE) CLASS F 155°C. THICKNESS 0.46 MM



*Slot wedge with high dielectric strength and good mechanical and thermal properties. The prestressed profile warrants very high rigidity and stability and contributes to a fast, safe installation*

- Working temperature +155°C
- Thickness 0.46 mm



### PRODUCT INFORMATION

---

Slot wedge NMNM 4-ply laminate, Nomex / Mylar / Nomex / Mylar with high dielectric strength and good mechanical and thermal properties

#### Typical applications

Suitable for winding applications

#### Properties

- Good mechanical properties
- Adapted for Class F varnishes
- Good electrical properties

#### Composition

- 4-ply laminate, Nomex/Mylar/Nomex/Mylar (calendered Nomex 50 µm)

#### Colour

- White

#### Packaging

- Bundles of 100 metres
- Length 1000 mm

#### Technical data


- Temperature Class F 155°C
- Dielectric strength -0.46 mm  $\geq$  24 kV
- Thickness tolerance  $\pm$  15%

*Product information for which Carbex bears no responsibility is provided by the manufacturer.*





## SLOT WEDGE NMNM 4-PLY LAMINATE (WHITE) CLASS F 155°C. THICKNESS 0.46 MM



ITEM NUMBER	TYPE	DIMENSIONS mm	PACK-AGING	DIELECTRIC STRENGTH KV	TENSILE STRENGTH N/mm <sup>2</sup>	WEIGHT g/m <sup>2</sup>	THICKNESS FILM μm
03 025 0102	SPÅRL NMNM 10 x 2	10 x 2 x 0.46 x 1000	100 m	≥ 24	≥ 300	460	250/23
03 025 0123	SPÅRL NMNM 12 x 3	12 x 3 x 0.46 x 1000	100 m	≥ 24	≥ 300	460	250/23
03 025 0144	SPÅRL NMNM 14 x 4	14 x 4 x 0.46 x 1000	100 m	≥ 24	≥ 300	460	250/23
03 025 0165	SPÅRL NMNM 16 x 5	16 x 5 x 0.46 x 1000	100 m	≥ 24	≥ 300	460	250/23
03 025 0186	SPÅRL NMNM 18 x 6	18 x 6 x 0.46 x 1000	100 m	≥ 24	≥ 300	460	250/23
03 025 0207	SPÅRL NMNM 20 x 7	20 x 7 x 0.46 x 1000	100 m	≥ 24	≥ 300	460	250/23
03 025 0228	SPÅRL NMNM 22 x 8	22 x 8 x 0.46 x 1000	100 m	≥ 24	≥ 300	460	250/23
03 025 0249	SPÅRL NMNM 24 x 9	24 x 9 x 0.46 x 1000	100 m	≥ 24	≥ 300	460	250/23
03 025 2610	SPÅRL NMNM 26 x 10	26 x 10 x 0.46 x 1000	100 m	≥ 24	≥ 300	460	250/23
03 025 2812	SPÅRL NMNM 28 x 12	28 x 12 x 0.46 x 1000	100 m	≥ 24	≥ 300	460	250/23

*Product information for which Carbex bears no responsibility is provided by the manufacturer.*

